


NEW DESIGN

MJ-HD3300F

With 1-28 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



4 seperated suction area to ensure continous printing job



1500W advanced Leadshine stable power servo motor



Advanced magnetic levitation transmission is standard



Intergrated anti-static device to improve machine stability



Special design to prevent material from wrinkling



Printhead Resolution

Konica1024i

	1*CMYK W 5 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>33m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>25m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	33m ² /h	1016x720	6pass	25m ² /h	1016x1080
	Print Speed	DPI								
4pass	33m ² /h	1016x720								
6pass	25m ² /h	1016x1080								
	2*CMYK 8 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>48m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>36m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	48m ² /h	1016x720	6pass	36m ² /h	1016x1080
	Print Speed	DPI								
4pass	48m ² /h	1016x720								
6pass	36m ² /h	1016x1080								
	2*CMYK+2W 10 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>33m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>25m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	33m ² /h	1016x720	6pass	25m ² /h	1016x1080
	Print Speed	DPI								
4pass	33m ² /h	1016x720								
6pass	25m ² /h	1016x1080								
	3*CMYK 12 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>68m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>45m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	68m ² /h	1016x720	6pass	45m ² /h	1016x1080
	Print Speed	DPI								
4pass	68m ² /h	1016x720								
6pass	45m ² /h	1016x1080								
	4*CMYK 16 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>95m²/h</td> <td>1016x720</td> </tr> <tr> <td>6pass</td> <td>70m²/h</td> <td>1016x1080</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	95m ² /h	1016x720	6pass	70m ² /h	1016x1080
	Print Speed	DPI								
4pass	95m ² /h	1016x720								
6pass	70m ² /h	1016x1080								

RICOH G5/G6

	1*CMYK W 3 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>30m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>24m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	30m ² /h	720x600	6pass	24m ² /h	720x900
	Print Speed	DPI								
4pass	30m ² /h	720x600								
6pass	24m ² /h	720x900								
	1*CMYK W V 4 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>30m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>24m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	30m ² /h	720x600	6pass	24m ² /h	720x900
	Print Speed	DPI								
4pass	30m ² /h	720x600								
6pass	24m ² /h	720x900								
	2*CMYK+1W 5 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>42m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>35m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	42m ² /h	720x600	6pass	35m ² /h	720x900
	Print Speed	DPI								
4pass	42m ² /h	720x600								
6pass	35m ² /h	720x900								
	3*CMYK 6 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>58m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>46m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	58m ² /h	720x600	6pass	46m ² /h	720x900
	Print Speed	DPI								
4pass	58m ² /h	720x600								
6pass	46m ² /h	720x900								
	3*CMYK+2W 8 pcs									
	<table border="1"> <thead> <tr> <th></th> <th>Print Speed</th> <th>DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>58m²/h</td> <td>720x600</td> </tr> <tr> <td>6pass</td> <td>46m²/h</td> <td>720x900</td> </tr> </tbody> </table>		Print Speed	DPI	4pass	58m ² /h	720x600	6pass	46m ² /h	720x900
	Print Speed	DPI								
4pass	58m ² /h	720x600								
6pass	46m ² /h	720x900								

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 4 rows, match all production need	Print Colors	CMYK LC LM W V
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collusion device, Independent Ink heating control, Neagtive inksupply, Print height sensor, 4 seperated suction area	Working Environment	5710*2350*1850mm,6000W Electricity Power, 20°C-28°C humidty40%-70%
Printing Heads	1-28pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A	Package Info	5830*2470*2200mm, 4800KG
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)		