# NEW DESIGN

MJ-HD5200PRO

With 8-40 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A

- Adapt to different diameter material by adjusting air pressure inside rollers
- Branded accessories used for high attrition areas
- Integrated Big functional machine control centre for high-efficiency
- Rigorous ink filtration design effectively avoid impurities from going into the ink supply system
- Support max 40 or more OEM konica printheads with higher speed

Printhead Resolution

Konica1024i

2*CMYK — 8 pcs

	Print Speed	DPI
4pass	55㎡/h	1016x720
6pass	42㎡/h	1016x1080

2*CMYK W — 10 pcs

	Print Speed	DPI
4pass	55㎡/h	1016x720
6pass	42㎡/h	1016x1080

3*CMYK — 12 pcs

	Print Speed	DPI
4pass	75㎡/h	1016x720
6pass	58㎡/h	1016x1080

3*CMYK LC LM — 18 pcs

	Print Speed	DPI
4pass	75㎡/h	1016x720
6pass	58㎡/h	1016x1080

4*CMYK LC LM — 24 pcs

	Print Speed	DPI
4pass	98㎡/h	1016x720
6pass	80㎡/h	1016x1080

3*CMYK W — 15 pcs

	Print Speed	DPI
4pass	75㎡/h	1016x720
6pass	58㎡/h	1016x1080

6*CMYK — 24 pcs

	Print Speed	DPI
4pass	180㎡/h	1016x720
6pass	108㎡/h	1016x1080

6*CMYK LC LM — 36 pcs

	Print Speed	DPI
4pass	180㎡/h	1016x720
6pass	108㎡/h	1016x1080

Print Software	Caldera/Phototprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 6 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collusion device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Print Colors	CMYK LC LM W V
Printing Heads	8-40pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A	Working Environment	6000W Electricity Power, 20℃-28℃ humidty40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	7880*2084*1846mm,4500KG